


HDMI Audio Converter with Dolby® Digital/DTS® Decoder



The AU-1H1DD is an advanced solution for de-embedding and down-mixing an audio signal from the HDMI input (up to Dolby Digital and DTS 2.0+Digital Out). Connect the AU-1H1DD between the source and your display via HDMI, and select 2CH LPCM or bypass. The digital audio outputs can be set to either 2CH LPCM or bypass. The L/R analogue outputs will always output down-mixed stereo (with audio up to Dolby® Digital and DTS® 2.0+Digital Out).

FEATURES

- HDCP 1.4 Compliant
- Supports resolutions VGA~WUXGA, 480i~1080p, 4K UHD@24/25/30Hz (RGB 4:4:4 & YUV 4:2:2), 4K UHD@ 60Hz (YUV 4:2:0), 4K/2K@24/25/30Hz (RGB 4:4:4 & YUV 4:2:2) and 4K/2K@ 60Hz (YUV 4:2:0) dependent upon the output display's EDID settings
- Supports simultaneous audio outputs on HDMI, analog R/L, Coaxial and Optical
- Choose between HDMI bypass and 2 Channel audio using the HDMI output switch
- Choose between SPDIF bypass and 2 Channel audio using the SPDIF output switch
- Supports digital coaxial and optical audio sampling rate output up to 96kHz
- Support Dolby Digital/DTS sampling rate up to 48kHz
- DTS Digital Surround Decoder technology
- Dolby Digital Decoder technology

SPECIFICATIONS

Input:	1x HDMI (1x Uncompressed AV and Data)
Output:	1x HDMI (1x Uncompressed AV and Data), 2x RCA (1x Stereo (L/R)), 1x Toslink (1x Dolby Digital / DTS / 2 Channel LPCM), 1x RCA (1x Coaxial Dolby Digital / DTS / 2 Channel LPCM)
Power:	5V/2.6A DC (US/EU standards, CE/FCC/UL certified)
Dimensions:	180mm (W) x 110mm (D) x 25mm (H)
Gross Weight:	868g
Net. Weight:	368g
Packaging:	Branded

