

## Cascadable 1 to 4 multi-screen controller



The 1 by 4 HDMI TV Wall controller allows an HDMI input source to be displayed, in full screen or single mode, on up to 4 HDMI displays (TV or monitor). Multiple units can be cascaded to extend the HDMI signal up to as many displays as needed. The unit features bezel correction function. A simple control application enables users to control single or multiple units. The device supports video timings up to WUXGA@60RB and 1080p@60Hz, audio format up to 7.1CH LPCM at 192kHz sampling rate based on input source EDID. Control can be achieved through software application, Telnet and RS-232.

### FEATURES

- HDMI, HDCP1.4 and DVI compliant
- Output source signal to 4 displays (2 by 2 Video wall) as a full screen or single image with adjustable Bezel Correction
- Cascade the HDMI signal up to as many as required
- Software application allows one button push to control all connected TV Wall devices
- Supports RS232 and Telnet controls
- Input resolutions support VGA~WUXGA and 480i~1080p
- Output resolutions support 720p~1080p
- Supports different input resolution and output resolution selectable from OSD menu. The factory default output resolution is native to the connected screen.
- Audio supports LPCM 2CH, 6CH, 8CH/AC3/DTS/Dolby Digital Plus/ Dolby TruHD & DTS-HD

### SPECIFICATIONS

Input:	1x HDMI (1x HDMI Uncompressed AV and Data) 1x 9pin Dsub (1x RS-232 Data) 1x RJ45 (1x IP Control) 1x USB Mini B (1x Service Port Propriety Data)
Output:	4x HDMI (4x HDMI Uncompressed AV and Data)
Power:	12V/3A DC (US/EU standards, CE/ FCC/UL certified)
Dimensions:	436mm (W) x 256mm (D) x 49mm (H)
Gross Weight:	3815g
Net. Weight:	2815g
Packaging:	Boxed

