

VEO-SPH48

DISTRIBUTION AMPLIFIER / SPLITTER

1x8 HDMI 2.0 DISTRIBUTION AMPLIFIER / SPLITTER



PRODUCT OVERVIEW

Ecler VEO-SPH48 is a professional 1x8 HDMI 2.0 distribution amplifier/splitter. It supports HDR formats and HDMI data rate up to 18Gbps, including 4K/UHD@60Hz video resolution with 4:4:4 chroma sampling. It includes EDID management in three different modes and it is HDCP 2.2 compliant. VEO-SPH48 guarantees seamless integration for all applications that require latest 4K/UHD and HDR sources and displays.

KEY FEATURES

- Simultaneously displays Ultra Hi-Definition source on up to eight Ultra HD displays
- Supports resolution up to Ultra HD 4Kx2K (4096x2160@60Hz YUV 4:4:4)
- Three EDID setting modes
- HDCP 2.2/1.4 Compliant
- Supports 36 bit Deep Color
- Supports LPCM 7.1, Dolby TrueHD, Dolby digital Plus, and DTS-HD Master Audio
- Supports HDR and 3D content
- Supports up to 18Gbps video data rate

APPLICATIONS

- Retail shops
- Fitness Center
- Sports Bar
- Restaurants
- Hotels
- Residential applications

1/4

TECHNICAL DATA

Audio and Video performances

Supported Resolutions Up to 4096x2160@60Hz
 4096x2160@24/25/30/50/60Hz, 3840x2160@24/25/30/50/60Hz, 2048x1080p
 1080p@23.98/24/25/29.97/30/50/59.94/60Hz, 1080i@50/59.94/60Hz, 720p@50/59.94/60Hz,
 576p, 576i, 480p, 480i

Colorspace RGB, YCbCr

Chroma Subsampling 4:4:4, 4:2:2, 4:2:0

Color depth 8-bit, 10-bit, 12-bit

HDR HDR 10

Signal Bandwidth 18 Gbps

HDCP 2.2/1.4 Compliant

Audio Formats PCM 2Ch, LPCM 5.1, LPCM 7.1, Dolby Digital, DTS 5.1, Dolby TrueHD, DTS-HD Master Audio

Sample Rate 32kHz, 44.1kHz, 48kHz, 88.2kHz, 96kHz, 176.4kHz, 192kHz

Bit rate up to 24-bit

HDMI Distance up to 10 meters (33 feet) with Ecler VEO cables

Operation Temperature -5 to +40°C (+41 to +104°F)

Humidity 5 to 90% (no condensation)

Power Consumption 5 W Maximim

Power Supply AC 100V ~ 240V 50/60Hz Output: DC 5V---1A

MISCELLANEOUS

Dimensions W x H x D 248mm x 17mm x 110mm (9.76" x 0.67" x 4.33")

Weight 610g / 1.34 lb

MECHANICAL DIAGRAMS

